*			09-27-6	<b>82 Rec'd PCT/PTC 72.6   SE#</b> 200
FORM (REV	PTO-139 11-98)		T OF COMMERCE PATENT AND TRADEMARK OFFICE	ATTORNEY'S DOCKET NUMBER
	T		TO THE UNITED STATES	K0208-013
ĺ		DESIGNATED/ELECTF	ED OFFICE (DO/EO/US)	U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR 1.5)
L		CONCERNING A FILIN	NG UNDER 35 U.S.C. 371	09/647279
		TIONAL APPLICATION NO. PCT/JP99/01542	INTERNATIONAL FILING DATE  March 26, 1999	PRIORITY DATE CLAIMED  March 27, 1998
		INVENTION  C SUPINCE BADDEL AND		
Pus.	SIL	IC SYRINGE BARREL AND	METHOD FOR IMPROVING THE S	SAME
APPI	ICAN	NT(S) FOR DO/EO/US		
		IIJIMA SEP 2 6 2000		
Appl	icant!	t herewith submits to the United Sta	Designated/Elected Office (DO/EO/US)	the following items and other information:
1.	×	This is a FIRST submission of it	items concerning a filing under 35 U.S.C. 371	
2.			QUENT submission of items concerning a filing	
Some street of the street of t	×	This is an express request to beg examination until the expiration	gin national examination procedures (35 U.S.c. of the applicable time limit set in 35 U.S.C.	.C. 371(f)) at any time rather than delay .371(b) and PCT Articles 22 and 39(1).
X	×	A proper Demand for Internation	nal Preliminary Examination was made by the	ne 19th month from the earliest claimed priority date.
APP.	X	A copy of the International Appli	lication as filed (35 U.S.C. 371 (c) (2))	
Object .			h (required only if not transmitted by the Inter	rnational Bureau).
		<ul> <li>b.      has been transmitted by</li> </ul>	y the International Bureau.	
**************************************	, t	c. is not required, as the a	application was filed in the United States Rec	ceiving Office (RO/US).
16	X		al Application into English (35 U.S.C. 371(c))	(2)).
7.87	Ķ			
8			the International Application under PCT Article	
gelia.			th (required only if not transmitted by the Inter-	ernational Bureau).
			by the International Bureau.	
		<ul> <li>c.  have not been made, ho</li> <li>d.  have not been made and</li> </ul>	owever, the time limit for making such amend	Iments has NOT expired.
9.			nd will not be made. Is to the claims under PCT Article 19 (35 U.S.)	5 451 ( ) 4W
10.	) [	An oath or declaration of the inve		C. 371(c)(3)).
11.	×		venion(s) (35 O.S.C. 371 (c)(4)). iminary Examination Report (PCT/IPEA/409).	
12.		A translation of the annexes to th	unmary Examination Report (PC 1/IPEA/409). The International Preliminary Examination Rep	
		(35 U.S.C. 3/1 (c)(5)).		Joint Middle 1 Of Filedole 50
		13 to 20 below concern document		
13.			ement under 37 CFR 1.97 and 1.98.	
14. 15.		An assignment document for reco	cording. A separate cover sheet in compliance	e with 37 CFR 3.28 and 3.31 is included.
15. 16.		A FIRST preliminary amendmen A SECOND or SUBSEQUENT		
17.		A substitute specification.	preliminary amenoniem.	
18.		A change of power of attorney and	ndlar address letter	
19.	X	Certificate of Mailing by Express		
20.	×	Other items or information:	IVIIII	
		a. References cited in Internati	tional Search Report	

26 SEP 2000

U.S. A	U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR 1.5) INTERNATIONAL APPLICATION NO.					ATTORNEY'S DOCKET NUMBER			
	09/647279 PCT/JP99/01542				K0208-013				
21.	The fol	lowing fees are	submitted:					CALCULATION	S PTO USE ONLY
BASI	C NATIONA	L FEE ( 37 CF	R 1.492 (a) (1)	(5)):				0112001111111	5 110 002 01.21
	Neither inter	mational prelim	inary examination CFR 1.445(a)(2)	n fee (37 CFR 1.482):	nor				
	and Internati	ional Search Re	port not prepared	by the EPO or JPO		\$	70.00		
×				7 CFR 1.482) not paid red by the EPO or JPO		<b>\$</b>	340.00		
	International	preliminary ex	amination fee (3'	7 CFR 1.482) not paid (2)) paid to USPTO .	to USPT	o \$	590.00		
	International	preliminary ex	amination fee pa	id to USPTO (37 CFR CT Article 33(1)-(4)	1.482)		570.00		
	International and all claim	l preliminary ex as satisfied prov	amination fee parisions of PCT A	id to USPTO (37 CFR ticle 33(1)-(4)	1.482)		\$96.00		
				ATE BASIC FE		OUNT	=	\$840.00	
Surcha	arge of \$130.0	0 for furnishing	the oath or decl	aration later than	□ 2	0 🗆	30		
month	s from the ear	liest claimed p	riority date (37 C	CFR 1.492 (e)).				\$0.00	
3971	AIMS	NUME	BER FILED	NUMBER EXT	RA	RA'			
25.3	claims	9	- 20 =	0		x \$18		\$0.00	
62.3	endent claims	2		0		x \$78		\$0.00	
Multi	ple Depender	t Claims (chec	k if applicable).			N X		\$260.00	
2				ABOVE CALC			=	\$1,100,00	
must a	tion of 1/2 for ilso be filed (	Note 37 CFR 1	l entity, if applic .9, 1.27, 1.28) <b>(c</b>	able. Verified Small E heck if applicable).	entity Sta	itement		\$0.00	
ALJ					SUB	TOTA	_ =	\$1,100.00	
Proces month	sing fee of \$1 s from the ear	30.00 for furni	shing the English riority date (37 (	translation later than CFR 1.492 (f)).	□ 2	0 🗆	30 +	\$0,00	
34				TOTAL NAT	IONAI	LFEE	=	\$1,100.00	
Fee fo	r recording th panied by an	e enclosed assi appropriate cov	gnment (37 CFR er sheet (37 CFR	1.21(h)). The assignm 3.28, 3.31) (check if	ent must	be		\$0.00	
(lath				TOTAL FEES	ENCL	OSED	=	\$1,100.00	· · · · · · · · · · · · · · · · · · ·
		-						Amount to be: refunded	\$
1	*							charged	\$
	A check in	the amount of		to cover the above t	fees is en	closed.			·
×		ge my Deposit e copy of this si	Account No. neet is enclosed.	16-0633 in the	amount o	f <b>\$1,100</b>	.00	to cover the abo	ve fees.
1									
X	The Comm	issioner is here	by authorized to	charge any fees which	may be re	equired, o	r credit :	any overpayment	
1	to Deposit.	Account No.	16-0633	A duplicate copy of the	is sheet i	s enclose	1.		
NOT) 1.137	E: Where an (a) or (b)) mı	appropriate t	me limit under	37 CFR 1.494 or 1.49 ore the application to	5 has no	t been me	t, a peti	ition to revive (37 C	CFR
SEND	ALL CORRI	ESPONDENCE	TO:			1	1 .	11 h) . [K]//	7)
<b>-</b>			10.		1	XW	lu W	1. [KUdalti	0
	M. DiMatte	o, Esq. ap, Webb & Ty	dor			SIGNA	TURE		
	Avenue of th	•	101		1 (	Tohn 1	M. DiM	Tattoo	
New	York, New Y	ork 10036-671	.0		,	NAME		Tatico	
1									
							lo. 32,6		
						REGIS	TRATIC	ON NUMBER	
1						9/26/0	0		
						DATE			

526 Rec'd PGT/CTC 26 SFP 2000

FESI00001/US

(1/10)

#### DESCRIPTION

#### PLASTIC SYRINGE BARREL AND METHOD FOR IMPROVING THE

SAME

5

15

20

25

#### Technical Field

The present invention relates to a plastic syringe barrel and a method for improving the same.

### Background Art

A pre-filled plastic syringe, that is, a plastic syringe with relatively large content volume into which a contrast medium is previously injected has been used in recent years. Since the contrast medium has relatively high viscosity, resistance is large in injecting the contrast medium into the body through blood vessels, the spiral cord, and the like. Hence, pressure injection by using a machine is generally performed. In this case, an extension tube or the like is connected to a nozzle portion of the plastic syringe barrel, and the contrast medium is injected under pressure into the body through the extension tube or the like, blood vessels, the spiral cord, and the like. When the contrast medium is injected into the body as described above, high pressure is applied to the inside of the plastic syringe, thereby creating a possibility that the connection portion of the of the plastic syringe barrel and the extension tube or the like becomes disconnected, and thus a luer lock portion for enabling firm connection to the extension tube or the like is formed in the nozzle portion of the plastic syringe barrel. This luer lock portion usually has structure in which a cylindrical space is formed between

5

an inner peripheral surface of an outer cylinder and an outer peripheral surface of an inner cylinder. The extension tube or the like is connected to the nozzle portion of the plastic syringe barrel by screwing a forward end of the extension tube or the like into the luer lock portion thus formed in the cylindrical space.

In this case, however, the connection of these two sometimes becomes loose due to the withdrawal of the screwed extension tube or the like. If injection is performed in loose connection, there is a possibility of the contrast medium leaking out of the connection portion due to high pressure applied during the injection of the contrast medium, which causes a problem.

An object of the present invention is to provide a means capable of firmly and surely connecting the extension tube or the like to the nozzle portion of the plastic syringe barrel and avoiding looseness of the connection.

#### Disclosure of the Invention

Claim 1 is characterized in that in a plastic syringe barrel in which an outer cylinder and an inner cylinder are formed in a nozzle portion of the plastic syringe barrel and in which a luer lock portion composed of a cylindrical space is formed between an inner peripheral surface of the outer cylinder and an outer peripheral surface of the inner cylinder, all or part of an inner surface of the luer lock portion is subjected to surface roughening treatment.

In the plastic syringe barrel in claim 1, as described in claim 2, the inner peripheral surface of the outer cylinder may be subjected to surface roughening treatment. Further, as described in claim 3, a helically continuous screw thread is formed on the inner peripheral surface of the outer cylinder,

25

5

and the surface of the screw thread and/or a screw root portion may be subjected to surface roughening treatment. Furthermore, as described in claim 4, the material of the plastic syringe barrel is cyclic polyolefin resin. Moreover, as described in claim 5, the surface roughening treatment is performed, for example, by blast treatment.

Claim 6 is characterized in that in a method for improving a plastic syringe barrel in which an outer cylinder and an inner cylinder are formed in a nozzle portion and in which a luer lock portion composed of a cylindrical space is formed between an inner peripheral surface of the outer cylinder and an outer peripheral surface of the inner cylinder, the connection strength of the luer lock portion is enhanced by forming all or part of an inner surface of the luer lock portion into a surface subjected to surface roughening treatment.

An extension tube or the like having a helical groove is screwed into the luer lock portion and connected thereto. What is connected to the luer lock is not limited to the extension tube, and may be a needle, a three-way cock, or the like. Also, its material is not specially limited.

In the plastic syringe barrel in claims 1 to 5, "subjected to surface roughening treatment" is not limited to a case where the inner surface of the luer lock portion is directly subjected to surface roughening treatment by subjecting all or part of the inner surface of the luer lock portion to blast treatment or the like. It also includes, for example, a case where in a mold used when the plastic syringe barrel is resin-molded, for example, a mold surface of a portion facing the inner surface of the luer lock portion is formed into a roughened surface and where the inner surface of the luer lock portion is indirectly subjected to surface roughening treatment by transferring the shape of the roughened surface of the mold surface to the inner surface of the

5

luer lock portion at the time of resin molding.

The blast treatment involves blowing hard fine particles such as emery onto the inner surface of the luer lock portion or the mold surface under high pressure to form small protruding and recessed portions thereon, thereby roughening the surface. In this invention, surface roughening treatment is performed by leaving small scratches on all or part of the inner face of the luer lock portion by forming a mold surface of a portion facing the inner surface of the luer lock portion into a roughened surface by being subjected to blast treatment or the like and transferring the shape of the roughened surface of the mold surface to the inner surface of the luer lock portion at the time of resin molding in a mold used when the plastic syringe barrel is resin-molded, or by directly subjecting the inner surface of the luer lock portion to blast treatment or the like. The aforesaid method of subjecting the inner surface of the luer lock portion or the mold surface to surface roughening treatment is not limited to blast treatment, and surface roughening treatment may be performed by forming small scratches on the inner surface of the luer lock portion or the mold surface by the use of a file or the like.

The material of the plastic syringe barrel is, for example, cyclic polyolefin resin, and polycarbonate resin, polymethacrylate resin, polypropylene resin, and the like are also available. The cyclic polyolefin resin is excellent particularly in the effect of being able to firmly and surely connecting the extension tube or the like.

## 25 Brief Description of Drawings

FIG. 1 is an explanatory view of a nozzle portion of a plastic syringe

25

5

barrel; and

FIG. 2 is an enlarged view showing the structure of a luer lock portion, and the lower half portion of FIG. 2 (a portion lower than a central line shown by an alternate long and short dash line) shows a section.

Best Mode for Carrying out the Invention

A preferred embodiment of the present invention will be explained below with reference to the attached drawings.

As shown in FIG. 1 and FIG. 2, a nozzle portion 2 is provided at a forward end of a plastic syringe barrel 1 is, for example, cyclic polyolefin resin. In the nozzle portion 2, an outer cylinder 3 and an inner cylinder 4 are formed, and a liquid such as a contrast medium is filled into the plastic syringe barrel 1. The liquid such as the contrast medium can be injected into the body from within the plastic syringe barrel 1 through a through-hole 5 formed so as to pierce through the middle of the inner cylinder 4.

A luer lock portion 6 composed of a cylindrical space is formed between an inner peripheral surface of the outer cylinder 3 and an outer peripheral surface of the inner cylinder 4. A helically continuous screw thread 7 is formed on the inner peripheral surface of the outer cylinder 3, and a screw root portion 8 is formed in the gap between adjacent ridges of the screw thread 7.

Surface roughening treatment is performed for an inner surface of the luer lock portion 6. The surface roughening treatment is performed by subjecting a mold surface of a portion facing the inner surface of the luer lock portion 6 to blast treatment and transferring the shape of a roughened surface

5

of the mold surface to the inner surface of the luer lock portion 6 at the time of resin molding, for example, in a mold used when the plastic syringe barrel 1 is resin-molded, or by directly subjecting the inner surface of the luer lock portion 6 to blast treatment. The surface roughening treatment may be performed for all of the inner surface of the luer lock portion 6, or may be performed for only part of the inner surface of the luer lock portion 6. For example, in the inner surface of the luer lock portion 6, only the inner peripheral surface of the outer cylinder 3 may be subjected to the surface roughening treatment. Moreover, for example, in the inner surface of the luer lock portion 6, the surfaces of both the helical screw thread 7 and the screw root portion 8 which are formed on the inner peripheral surface of the outer cylinder 3 may be subjected to the surface roughening treatment. Furthermore, the surface roughening treatment may be performed for only the surface of either one of the helical screw thread 7 or the screw root portion 8 formed on the inner peripheral surface of the outer cylinder 3.

In the nozzle portion 2 at the forward end of the plastic syringe barrel 1 structured as above, for example, by screwing a forward end of an extension tube not illustrated into the luer lock portion 6 composed of the cylindrical space, a helical groove formed in a peripheral surface of the extension tube not illustrated can be brought into engagement with the helical screw thread 7 formed on the inner peripheral surface of the outer cylinder 3, whereby the extension tube or the like can be firmly and surely connected to the nozzle portion 2 of the forward end of the plastic syringe barrel 1.

### 25 Industrial Availability

According to the invention in claims 1 to 6, a plastic syringe barrel

and an extension tube or the like can be firmly and surely connected, and the connection does not become loose since friction between them is increased by surface roughening treatment. Consequently, there is no fear of a contrast medium leaking out of a connection portion when the contrast medium is injected into the body from within the plastic syringe barrel through blood vessels, the spinal cord, or the like.

25

5

#### Claims

1. A plastic syringe barrel in which an outer cylinder and an inner cylinder are formed in a nozzle portion of the plastic syringe barrel and in which a luer lock portion composed of a cylindrical space is formed between an inner peripheral surface of the outer cylinder and an outer peripheral surface of the inner cylinder,

wherein all or part of an inner surface of said luer lock portion is subjected to surface roughening treatment.

2. The plastic syringe barrel according to claim 1,

wherein said inner peripheral surface of said outer cylinder is subjected to surface roughening treatment.

3. The plastic syringe barrel according to claim 1,

wherein a helically continuous screw thread is formed on said inner peripheral surface of said outer cylinder, and the surface of said screw thread and/or a screw root portion is subjected to surface roughening treatment.

- The plastic syringe barrel according to claim 1, wherein the material of said plastic syringe barrel is cyclic polyolefin resin.
- 5. The plastic syringe barrel according to any one of claims 1, 2, 3, and 4, wherein said surface roughening treatment is blast treatment.

6. A method for improving a plastic syringe barrel in which an outer cylinder and an inner cylinder are formed in a nozzle portion and in which a luer lock portion composed of a cylindrical space is formed between an inner peripheral surface of the outer cylinder and an outer peripheral surface of the inner cylinder,

wherein the connection strength of said luer lock portion is enhanced by forming all or part of an inner surface of said luer lock portion into a surface subjected to surface roughening treatment.

#### Abstract

A plastic syringe barrel having a luer lock portion is characterized in that the inside of the luer lock portion is formed into a roughened surface by means of blast treatment, thereby enhancing the connection strength of the luer lock portion.

FIG.1





FIG.2



8.03mm

# **EXPLANATION OF CODES**

1	PLASTIC SYRINGE BARREL
1	PLASTIC SYKINGE BARREL

- 2 NOZZLE PORTION
- 3 OUTER CYLINDER
- 4 INNER CYLINDER
- 5 THROUGH-HOLE
- 6 LUER LOCK PORTION
- 7 SCREW THREAD
- 8 SCREW ROOT PORTION

PTD.SB.81 (92.1)

Addroved for use "incough 10.31.000, 2006 685-0005

Addroved for use "incough 10.31.000, 2006 685-0005

J.S. Palein, and "indomatic Office, U.S. DEP ARTMENT OF DOMMETOD

Under the Paperwork Reduction Act, or 1995, no persons are required to respond to a collection of information unless to possavial ward CMB control number.

## POWER OF ATTORNEY OR AUTHORIZATION OF AGENT

Application Number	1 09/647, 279
Filing Date	September 26, 2000
First Named Inventor	Kazumi Iijima
.Title	Plastic Syringe Barrel
Group Art Unit	t.b.a and Method For
Examiner Name	t.b.a Improving The Sam
Attorney Docket Number	K0208-0013

I hereby appoint:  Practitioners at Customer Number  OR	Place Customer Numo 2 3 1 (2-3) Label here
Practitioner(s) named below:	Registration Number
name	Redistration
	·
as my/our attorney(s) or agent(s) to prosecute the application	
business in the United States Patent and Trademark Office co	
Please change the correspondence address for the above-ide	entified application to:
The above-mentioned Customer Number	
OR Practitioners at Customer Number	Place Customer Number Bar Code
OR	Laper nere
Firm or	
Individual Name	
Address	
Accress	
City	State Zp
Country	
Telephone	Fax
I am the	
Applicant/Inventor	
	74
Assignee of record of the entire interest. See 37 CFR 3 Statement under 37 CFP 3 73(a) is enclosed. Form P7	7". TOISB:98!
SIGNATURE of Applicant or Assign	ee of Record
Name Kazumi Digimo	
Sonatura Karanmi Delimin	
23/6   Z2/6/200/	rimur lagreyar di yelikilire lagur iti yu umtimu u
A BOOK A STATE OF THE STATE OF	=
Electric comments	

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION FOR UTILITY OR
DESIGN
PATENT APPLICATION
(37 CFR 1 63)

Declaration Submitted with Initial

Filing

Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)

Attorney Docket Number		K0208-0013		
First Named Inventor		Kazumi Iijima		
COMPL	ETE IF	KNOWN		
Application Number	09/647, 279			
Filing Date Sep		tember 26, 2000		
Group Art Unit	t.b	.a.		
Examiner Name t.b		.a.		

#### As a below named inventor, I hereby declare that:

My residence, mailing address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

> Plastic Syringe Barrel and Method For Improving The Same

> > (Title of the Invention)

the specification of which

is attached hereto

OP

17

i pro

13

> æ

> 300

falls.

was filed on (MM/DD/YYYY)

09/26/2000

as United States Application Number or PCT International

Application Number | 09/647,279

and was amended on (MM/DD/YY)

(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above

Lacknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56, including for continuation-in-part applications, material information which became available between the filling date of the prior application and the national or PCT international filling date of the continuation-no-art adollication.

hereby claim foreign priority penefits under 35 U.S.C. 119(a)-(d) or (f), or 365(b) of any foreign application(s) for patent, inventors or plant freeders rights certificates), or 365(a) or any PCT international application which determines not patient, inventors or plant freeders rights certificates), or 365(a) or any PCT international application which destines on the second of the second process application on which priority is claimed

Prior Foreign Application	1	Foreign Filing Date	Priority	Certified Copy Attached	,
Number(s)	Country	(MM/DD/YYYY)	Not Claimed :	YES NO	
10/80688 PCT/JP99/01542	JP PCT	3/27/1998 3/26/1999			

Additional foreign application of moets are listed on a supplemental propriet data sheet PTC SB.028 attached hereig

PTC/S8/01 (03-01)
Approved for use through 10/31/202, 20MB 0631-0022
U.S. Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

# DECLARATION — Utility or Design Patent Application

	_					
Direct all correspondence to: X Customer NL or Bar Code		23,723		OR C	orrespondence address below	
Name						
Address						
City			State		ZIP	
Country	Telepi	hone			Fax	
I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or impresonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.						
NAME OF SOLE OR FIRST INVENTOR:		A petition ha	s been	filed for this un	signed inventor	
Given Name (first and middle [if any]) Kazumi			Family I			
Inventor's Signature Kuzumi J	iji	MC			Date 22/06/2001	
Residence: City Gumma		State	c	Japan ountry	Citizenship Japan	
Mailing Address 892-2, Tsunatorimach	ıi,	Isesaki-Sh	i			
city Gumma		State	1 -	372 <b>-</b> 0812 ZIP	Country Japan	
NAME OF SECOND INVENTOR:	Δ	petition has	been fil	led for this unsig	gned inventor	
iven Name Family Name irst and middle [if any]) or Surname						
nventor's Signature					Date	
esidence: City	Sta	te	Cour	itry	Citizenship	
lailing Address						
ity	Sta	ite	ZIP		Country	
Additional inventors are being named on thes						